



GB Fitting Instructions for Basic Carrier




x 4




x 4




x 4



x 4



x 4



MAX kg
 **W/P WHD**

MAX kg
 **W/P WHD**

Chevrolet							
Corsa C, 3dr Hatch 00- 06	US	50	50	Zafira, 5dr MPV 99- 05	US	50	50
Daewoo							
Cielo, 3dr Hatch 94- 98	EU	50	50	Cielo, 3dr Hatch Sep 95-Jul 98	NZ	50	50
Cielo, 4dr Sedan 94- 98	EU	50	50	Cielo, 4dr Sedan 95- 97	ZA	50	50
Cielo, 4dr Sedan Aug 95-Apr 98	AU	50	50	Cielo, 5dr Hatch 94- 98	EU	50	50
Cielo, 5dr Hatch Aug 95-Apr 98	AU	50	50	Cielo, 5dr Hatch Sep 95-Jul 98	NZ	50	50
Le Mans, 4dr Sedan 87- 94	EU	75	75	Le Mans, 5dr Hatch 87- 94	EU	75	75
Holden							
Astra, 5dr Hatch Dec 98-Jun 04	NZ	75	75	Astra TS, 5dr Hatch Dec 98-Oct 04	AU	75	75
Barina, 3dr Hatch 00- 06	NZ	50	50	Barina, 3dr Hatch 00- 06	AU	50	50
Barina, 5dr Hatch Jul 93-Jul 05	NZ	50	50	Barina SB, 3dr Hatch Apr 94-Mar 01	AU	50	50
Barina SB, 5dr Hatch Apr 94-Mar 05	AU	50	50	Calibra, 2dr Coupe 89- 97	AU	75	75
Calibra, 2dr Coupe 89- 97	NZ	75	75	Zafira, 5dr MPV 99- 05	AU	50	50
Land Rover							
Range Rover, 5dr SUV 95- 01	EU	50	50	Range Rover, 5dr SUV 95- 01	ZA	50	50
Range Rover, 5dr SUV Jul 95-Dec 02	NZ	50	50	Range Rover, 5dr SUV May 95-Jul 02	AU	50	50
Opel							
Astra, 5dr Hatch 98- 03	EU	75	75	Calibra, 2dr Coupe 89- 97	EU	75	75
Calibra, 2dr Coupe 89- 97	NZ	75	75	Corsa, 5dr Hatch 93- 05	ZA	50	50
Corsa, 5dr Hatch 93- 05	EU	50	50	Corsa C, 3dr Hatch 00- 06	EU	50	50
Zafira, 5dr MPV 98- 04	EU	50	50	Zafira, 5dr MPV 98- 04	ZA	50	50
Pontiac							
Le Mans, 4dr Sedan Sep 87-Mar 93	NZ	75	75				
Subaru							
Traviq, 5dr MPV 99- 05	NZ	50	50				
Vauxhall							
Astra, 5dr Hatch 98- 03	EU	75	75	Calibra, 2dr Coupe 89- 97	EU	75	75
Corsa, 5dr Hatch 93- 05	EU	50	50	Corsa C, 3dr Hatch 00- 06	EU	50	50
Zafira, 5dr MPV 98- 04	EU	50	50				

First Time Installation



- Remove parts from packaging and check contents. Contact your Prorack dealer if parts are missing or damaged.



- This kit fits type A, B, C and D.
- These instructions show type A crossbar fitted. They also apply to type B, C and D.




- Use keys to remove covers.



- Use hex screwdriver to reverse adjusting screw 10 turns.



- Press adjusting screw and pull crossbar legs out. Refer to the crossbar instructions for crossbar adjustment.
- Ensure each end of the crossbar is adjusted equally.



- Set bars to length (refer to the crossbar instructions for crossbar adjustment).
- Please check the rear of this manual for information relating specifically to your vehicle.



- Tighten adjusting screw to 5 Nm.




- Remove clamp block by pressing backwards.



- Select plastic internal block (from fitting kit) and insert into foot.
- Repeat for all legs.



- Fit rubber pads (supplied with fitting kit) to foot. Pad may vary in shape to that shown.
- Make sure the pad fits into the holes underneath the foot.



- Open fixed point cover by sliding with downwards pressure.



- Locate clamp onto seam flange as shown (hook outboard, blade inboard).
- Ensure hook is engaged under flange return and clamp blade is behind the flange.
- Repeat for all four positions.



- Place crossbar foot over clamp.
- Fixed-point opening should be covered by the pad.



- Place washer over clamp thread as shown.
- Ensure that tab is inserted into clamp block.



- Place one hand on the leg and apply downward pressure.
- Tighten the red plastic knob.



- Ensure the red plastic knob is in the position shown when fully tightened.
- Repeat for all legs.



- Check crossbar is securely attached to the vehicle.
- Use keys to fit and lock covers

CAUTION:
Recheck all fasteners immediately after a load is applied to the crossbars.
Regularly check screws are tight.

Maintenance


- Clean the car roof and surfaces of the product that will be in contact with the car roof.
- Follow the fitting instructions for fitting the product to your vehicle. Make sure all steps are carried out in order.
- Set crossbars a minimum distance of 700mm apart where no other distance is specified in the fitting instructions. This is especially important when carrying long loads.
- Check unit is securely attached whenever you refit it to the vehicle. If the unit feels loose, refer to the fitting instructions and readjust.
- Some sunroofs and radio antennae cannot be used when the product is fitted.
- Do not modify this product.
- Refer to the maximum permitted load capacity specified in the fitting instructions. Do not exceed the vehicle manufacturers roof load rating if it is lower than the maximum load capacity specified in the fitting instructions.
- Loads should not overhang the sides of the product and be evenly distributed with the lowest possible centre of gravity.
- Long loads should be secured with non-elastic straps to the front and rear of the vehicle.
- Objects with pointed ends (skis) should be carried with the pointed ends to the rear of the vehicle.
- Remove all loose or removable objects from the load prior to loading.
- Make sure all loads are securely fastened with non-elastic straps. Check regularly during longer journeys.

- A loaded roof rack system can alter the performance of your vehicle. Be especially aware of the effects of side winds, changing of direction, and braking performance. Avoid rapid acceleration and deceleration. Drive carefully.
- Note that the total height of the vehicle increases when upright loads are carried.
- Products should be locked during transport if they have locks fitted.
- Check and replace worn out or defective parts.
- Keep the product clean and maintained.
- Never drive into a car wash with the roof rack system fitted.
- Lubricate locks and adjusting screws at regular intervals.
- Remove the products from the vehicle when not in use. Make sure all loose parts are stored safely.




● Hubco Automotive Ltd
P. O. Box 11017
Christchurch
NEW ZEALAND

www.whispbar.com

A = -



A = +



Chevrolet Corsa C, 3dr Hatch 00- 06 (US)

A	B	C	1	2	3
-40cm	30cm	-	778mm	753mm	-
-15 3/4"	11 13/16ths"	-	30 5/8"	29 5/8"	-

Chevrolet Zafira, 5dr MPV 99- 05 (US)

-2cm	78cm	-	795mm	765mm	-
- 13/16ths"	30 11/16ths"	-	31 5/16ths"	30 1/8"	-

Daewoo Cielo, 3dr Hatch 94- 98 (EU)

-	-	-	-	-	-
---	---	---	---	---	---

Daewoo Cielo, 3dr Hatch Sep 95-Jul 98 (NZ)

-	-	-	-	-	-
---	---	---	---	---	---

Daewoo Cielo, 4dr Sedan 94- 98 (EU)

-	-	-	-	-	-
---	---	---	---	---	---

Daewoo Cielo, 4dr Sedan 95- 97 (ZA)

-	-	-	-	-	-
---	---	---	---	---	---

Daewoo Cielo, 4dr Sedan Aug 95-Apr 98 (AU)

-	-	-	-	-	-
---	---	---	---	---	---

Daewoo Cielo, 5dr Hatch 94- 98 (EU)

-	-	-	-	-	-
---	---	---	---	---	---

Daewoo Cielo, 5dr Hatch Aug 95-Apr 98 (AU)

-	-	-	-	-	-
---	---	---	---	---	---

Daewoo Cielo, 5dr Hatch Sep 95-Jul 98 (NZ)

-	-	-	-	-	-
---	---	---	---	---	---

Daewoo Le Mans, 4dr Sedan 87- 94 (EU)

-	-	-	-	-	-
---	---	---	---	---	---

Daewoo Le Mans, 5dr Hatch 87- 94 (EU)

-	-	-	-	-	-
---	---	---	---	---	---

Holden Astra, 5dr Hatch Dec 98-Jun 04 (NZ)

-14cm	51cm	-	770mm	775mm	-
-5 1/2"	20 1/16ths"	-	30 5/16ths"	30 1/2"	-

Holden Astra TS, 5dr Hatch Dec 98-Oct 04 (AU)

-14cm	51cm	-	770mm	775mm	-
-5 1/2"	20 1/16ths"	-	30 5/16ths"	30 1/2"	-

Holden Barina, 3dr Hatch 00- 06 (AU)

-40cm	30cm	-	778mm	753mm	-
-15 3/4"	11 13/16ths"	-	30 5/8"	29 5/8"	-

Holden Barina, 3dr Hatch 00- 06 (NZ)

-40cm	30cm	-	778mm	753mm	-
-15 3/4"	11 13/16ths"	-	30 5/8"	29 5/8"	-

Holden Barina, 5dr Hatch Jul 93-Jul 05 (NZ)

24.5cm	42.5cm	-	740mm	730mm	-
9 5/8"	16 3/4"	-	29 1/8"	28 3/4"	-

Holden Barina SB, 3dr Hatch Apr 94-Mar 01 (AU)	-	-	-	740mm	730mm	-
	-	-	-	29 1/8"	28 3/4"	-
Holden Barina SB, 5dr Hatch Apr 94-Mar 05 (AU)	24.5cm	42.5cm	-	740mm	730mm	-
	9 5/8"	16 3/4"	-	29 1/8"	28 3/4"	-
Holden Calibra , 2dr Coupe 89- 97 (AU)	-48cm	11cm	-	780mm	760mm	-
	-18 7/8"	4 5/16ths"	-	30 11/16ths"	29 15/16ths"	-
Holden Calibra , 2dr Coupe 89- 97 (NZ)	-48cm	11cm	-	780mm	760mm	-
	-18 7/8"	4 5/16ths"	-	30 11/16ths"	29 15/16ths"	-
Holden Zafira , 5dr MPV 99- 05 (AU)	-2cm	78cm	-	795mm	765mm	-
	- 13/16ths"	30 11/16ths"	-	31 5/16ths"	30 1/8"	-
Land Rover Range Rover , 5dr SUV 95- 01 (EU)	-32cm	37.5cm	106.5cm	940mm	940mm	925mm
	-12 5/8"	14 3/4"	41 15/16ths"	37 "	37 "	36 7/16ths"
Land Rover Range Rover , 5dr SUV 95- 01 (ZA)	-32cm	37.5cm	106.5cm	940mm	940mm	925mm
	-12 5/8"	14 3/4"	41 15/16ths"	37 "	37 "	36 7/16ths"
Land Rover Range Rover , 5dr SUV Jul 95-Dec 02 (NZ)	-32cm	37.5cm	106.5cm	940mm	940mm	925mm
	-12 5/8"	14 3/4"	41 15/16ths"	37 "	37 "	36 7/16ths"
Land Rover Range Rover , 5dr SUV May 95-Jul 02 (AU)	-32cm	37.5cm	106.5cm	940mm	940mm	925mm
	-12 5/8"	14 3/4"	41 15/16ths"	37 "	37 "	36 7/16ths"
Opel Astra , 5dr Hatch 98- 03 (EU)	-14cm	51cm	-	770mm	775mm	-
	-5 1/2"	20 1/16ths"	-	30 5/16ths"	30 1/2"	-
Opel Calibra , 2dr Coupe 89- 97 (EU)	-48cm	11cm	-	780mm	760mm	-
	-18 7/8"	4 5/16ths"	-	30 11/16ths"	29 15/16ths"	-
Opel Calibra , 2dr Coupe 89- 97 (NZ)	-48cm	11cm	-	780mm	760mm	-
	-18 7/8"	4 5/16ths"	-	30 11/16ths"	29 15/16ths"	-
Opel Corsa , 5dr Hatch 93- 05 (EU)	24.5cm	42.5cm	-	740mm	730mm	-
	9 5/8"	16 3/4"	-	29 1/8"	28 3/4"	-
Opel Corsa , 5dr Hatch 93- 05 (ZA)	24.5cm	42.5cm	-	740mm	730mm	-
	9 5/8"	16 3/4"	-	29 1/8"	28 3/4"	-
Opel Corsa C, 3dr Hatch 00- 06 (EU)	-40cm	30cm	-	778mm	753mm	-
	-15 3/4"	11 13/16ths"	-	30 5/8"	29 5/8"	-
Opel Zafira , 5dr MPV 98- 04 (EU)	-2cm	78cm	-	795mm	765mm	-
	- 13/16ths"	30 11/16ths"	-	31 5/16ths"	30 1/8"	-
Opel Zafira , 5dr MPV 98- 04 (ZA)	-2cm	78cm	-	795mm	765mm	-
	- 13/16ths"	30 11/16ths"	-	31 5/16ths"	30 1/8"	-
Pontiac Le Mans , 4dr Sedan Sep 87-Mar 93 (NZ)	-	-	-	-	-	-
	-	-	-	-	-	-
Subaru Traviq , 5dr MPV 99- 05 (NZ)	-2cm	78cm	-	795mm	765mm	-
	- 13/16ths"	30 11/16ths"	-	31 5/16ths"	30 1/8"	-
Vauxhall Astra , 5dr Hatch 98- 03 (EU)	-14cm	51cm	-	770mm	775mm	-
	-5 1/2"	20 1/16ths"	-	30 5/16ths"	30 1/2"	-
Vauxhall Calibra , 2dr Coupe 89- 97 (EU)	-48cm	11cm	-	780mm	760mm	-
	-18 7/8"	4 5/16ths"	-	30 11/16ths"	29 15/16ths"	-
Vauxhall Corsa , 5dr Hatch 93- 05 (EU)	24.5cm	42.5cm	-	740mm	730mm	-
	9 5/8"	16 3/4"	-	29 1/8"	28 3/4"	-
Vauxhall Corsa C, 3dr Hatch 00- 06 (EU)	-40cm	30cm	-	778mm	753mm	-
	-15 3/4"	11 13/16ths"	-	30 5/8"	29 5/8"	-
Vauxhall Zafira , 5dr MPV 98- 04 (EU)	-2cm	78cm	-	795mm	765mm	-
	- 13/16ths"	30 11/16ths"	-	31 5/16ths"	30 1/8"	-