


GB Fitting Instructions for Basic Carrier










	MAX kgs				MAX kgs			
		W/P	WHD			W/P V	VHD	
Hyundai								
Accent , 5dr Hatch 11-+	ZA	75	75	Accent, 5dr Hatch 11-+	NZ	75	75	
Accent , 5dr Hatch 11-+	EU	75	75	Accent, 5dr Hatch 11-+	US	75	75	
Accent , 5dr Hatch 11-+	AU	75	75	i30 , 5dr Hatch 07-Dec 11	EU	75	75	
i30 , 5dr Hatch 12-+	AU	50	50	i30 , 5dr Hatch 12-+	NZ	50	50	
i30 , 5dr Hatch 12-+	EU	50	50	i30 , 5dr Hatch 12-+	US	50	50	
i30 , 5dr Hatch 12-+	ZA	50	50	i30 , 5dr Hatch Oct 07-Dec 11	NZ	75	75	
i30 , 5dr Hatch Oct 07-Dec 11	AU	75	75					
Kia								
Cee'd, 5dr Hatch 06-+	EU	75	75	Cee'd, 5dr Hatch 07-+	ZA	75	75	
Mazda								
2, 5dr Hatch 07-+	ZA	50	50	2, 5dr Hatch 07-+	EU	50	50	
2, 5dr Hatch 10-+	US	50	50	3, 4dr Sedan 09-+	AU	75	75	
3, 4dr Sedan 09-+	NZ	75	75	3, 4dr Sedan 09-+	EU	75	75	
3 , 4dr Sedan 10-+	US	75	75	3,5dr Hatch 09-+	AU	75	75	
3 , 5dr Hatch 09-+	NZ	75	75	3,5dr Hatch 09-+	EU	75	75	
3 , 5dr Hatch May 09-+	US	75	75					

First Time Installation



 Remove parts from inside the package and check. Contact your dealer if any parts are missing or damaged.



- This kit fits type A, B, C and D.
- These instructions show type A crossbar fitted. They also apply to type B, C and D.




Use keys to remove covers.



 Use hex screwdriver to reverse adjusting screw 10 turns.



- Press adjusting screw and pull crossbar legs out. Refer to the crossbar instructions for crossbar adjustment.
- Ensure each end of the crossbar is adjusted equally.



- Adjust crossbar in or out to suit vehicle.
 Refer to the crossbar instructions for crossbar adjustment.
- Please check the rear of this manual for information relating specifically to your vehicle.



• Tighten adjusting screw to 5 Nm (3.7 ft lb).




 Remove plastic clamp block by gripping bar leg with fingers and push firmly with thumbs until clamp block drops out behind leg.



- Select plastic internal block (from fitting kit) and insert into foot.
- Repeat for all legs.



 Refer to the underside of the pad for the part number.



- Letters refer to the pad part numbers and position.
- Pad Part Number:

A = 11-04-257

B = 11-04-256

C = 11-04-244




- Fit rubber pads (supplied with fitting kit) to foot. Pad may vary in shape to that shown.
- Make sure the pad fits into the holes underneath the foot.

Fitment




• Open or remove fixed-point covers.




- Select grubscrews and screw into the vehicle's fixed points.
- Grubscrew length:Mazda = 60mm (2 3/8")Hyundai = 70mm (2 3/4")
- Do not over tighten.
- Repeat for all four positions.



• Place crossbar foot over grubscrews.



• Tighten the red plastic knob. The side with the nut showing should be facing up.



- In the fully tightened position, the knobs should be parallel with the vehicle.
- Repeat for all four positions.



- Check crossbar is securely attached to the vehicle.
- Use keys to fit and lock covers

CAUTION:

Recheck all fasteners immediately after a load is applied to the crossbars.


Regularly check screws are tight.


Maintenance


- Clean the car roof and surfaces of the product that will be in contact with the car roof.
- Follow the fitting instructions for fitting the product to your vehicle. Make sure all steps are carried out in order.
- Set crossbars a minimum distance of 700mm (27 1/2") apart where no other distance is specified in the fitting instructions. This is especially important when carrying long loads.
- Check unit is securely attached whenever you refit it to the vehicle. If the unit feels loose, refer to the fitting instructions and readjust.
- Some glass/panoramic roofs and radio antennae may not be able to be used when the product is fitted.
- Do not modify this product.
- Refer to the maximum permitted load capacity specified in the fitting instructions.
 Do not exceed the vehicle manufacturers roof load rating if it is lower than the maximum load capacity specified in the fitting instructions.
- Loads should not overhang the sides of the product and be evenly distributed with the lowest possible centre of gravity.
- Long loads should be secured with nonelastic straps to the front and rear of the vehicle.
- Objects with pointed ends (e.g. ski poles) should be carried with the pointed ends to the rear of the vehicle.
- Remove all loose or removable objects from the load prior to loading.
- Make sure all loads are securely fastened with non-elastic straps. Check regularly during longer journeys.

- A loaded roof rack system can alter the performance of your vehicle. Be especially aware of the effects of side winds, changing of direction, and braking performance. Avoid rapid acceleration and deceleration. Drive carefully.
- Note that the total height of the vehicle increases when upright loads are carried.
- Products should be locked during transport if they have locks fitted.
- Check and replace worn out or defective parts.
- Keep the product clean and maintained.
- Never drive into a car wash with the roof rack system fitted.
- Lubricate locks and adjusting screws at regular intervals.
- Remove the products from the vehicle when not in use. Make sure all loose parts are stored safely.
- Yakima Australia Pty Ltd 17 Hinkler Court Brendale QLD 4500 AUSTRALIA

www.whispbar.com www.whispbar.co.nz www.whispbar.co.uk www.whispbar.co.za www.whispbar.eu www.whispbar.ca









Hyundai Accent , 5dr Hatch 11-+ (AU)

Hyundai Accent , 5dr Hatch 11-+ (EU)

Hyundai Accent, 5dr Hatch 11-+ (NZ)

Hyundai Accent , 5dr Hatch 11-+ (US)

Hyundai Accent , 5dr Hatch 11-+ (ZA)

Hyundai i30 , 5dr Hatch 07-Dec 11 (EU)

Hyundai i30 , 5dr Hatch 12-+ (AU)

Hyundai i30 , 5dr Hatch 12-+ (EU)

Hyundai i30 , 5dr Hatch 12-+ (NZ)

Hyundai i30 , 5dr Hatch 12-+ (US)

Hyundai i30 , 5dr Hatch 12-+ (ZA)

Hyundai i30 , 5dr Hatch Oct 07-Dec 11 (AU)

Hyundai i30 , 5dr Hatch Oct 07-Dec 11 (NZ)

Kia Cee'd, 5dr Hatch 06-+ (EU)

Kia Cee'd, 5dr Hatch 07-+ (ZA)

Mazda 2 , 5dr Hatch 07-+ (EU)

Mazda 2 , 5dr Hatch 07-+ (ZA)

			X				
Α	В	С	1	2	3		
-250mm -9 13/16ths"	650mm 25 9/16ths"	-	834mm 32 13/16ths"	840mm 33 1/16ths"	-		
-250mm -9 13/16ths"	650mm 25 9/16ths"	-	834mm 32 13/16ths"	840mm 33 1/16ths"	-		
-250mm -9 13/16ths"	650mm 25 9/16ths"	-	834mm 32 13/16ths"	840mm 33 1/16ths"	-		
-250mm -9 13/16ths"	650mm 25 9/16ths"	-	834mm 32 13/16ths"	840mm 33 1/16ths"	-		
-250mm -9 13/16ths"	650mm 25 9/16ths"	-	834mm 32 13/16ths"	840mm 33 1/16ths"	-		
-90mm -3 9/16ths"	730mm 28 3/4"	-	834mm 32 13/16ths"	804mm 31 5/8"	-		
-195mm -7 11/16ths"	590mm 23 1/4"	-	874mm 34 7/16ths"	840mm 33 1/16ths"	-		
-195mm -7 11/16ths"	590mm 23 1/4"	-	874mm 34 7/16ths"	840mm 33 1/16ths"	-		
-195mm -7 11/16ths"	590mm 23 1/4"	-	874mm 34 7/16ths"	840mm 33 1/16ths"	-		
-195mm -7 11/16ths"	590mm 23 1/4"	-	874mm 34 7/16ths"	840mm 33 1/16ths"	-		
-195mm -7 11/16ths"	590mm 23 1/4"	-	874mm 34 7/16ths"	840mm 33 1/16ths"	-		
-90mm -3 9/16ths"	730mm 28 3/4"	-	834mm 32 13/16ths"	804mm 31 5/8"	-		
-90mm -3 9/16ths"	730mm 28 3/4"	-	834mm 32 13/16ths"	804mm 31 5/8"	-		
-90mm -3 9/16ths"	730mm 28 3/4"	-	825mm 32 1/2"	795mm 31 5/16ths"	-		
-90mm -3 9/16ths"	730mm 28 3/4"	-	825mm 32 1/2"	795mm 31 5/16ths"	-		
-130mm -5 1/8"	580mm 22 13/16ths"	-	795mm 31 5/16ths"	725mm 28 9/16ths"	-		
-130mm -5 1/8"	580mm 22 13/16ths"	-	795mm 31 5/16ths"	725mm 28 9/16ths"	-		

Mazda 2, 5dr Hatch 10-+ (US)	-130mm	580mm	-	795mm	725mm	-
, ,	-5 1/8"	22 13/16ths"	-	31 5/16ths"	28 9/16ths"	-
Mazda 3, 4dr Sedan 09-+ (AU)	-290mm	360mm	-	873mm	847mm	-
	-11 7/16ths"	14 3/16ths"	-	34 3/8"	33 3/8"	-
Mazda 3, 4dr Sedan 09-+ (EU)	-290mm	360mm	-	873mm	847mm	-
• •	-11 7/16ths"	14 3/16ths"	-	34 3/8"	33 3/8"	-
Mazda 3, 4dr Sedan 09-+ (NZ)	-290mm	360mm	-	873mm	847mm	-
• •	-11 7/16ths"	14 3/16ths"	-	34 3/8"	33 3/8"	-
Mazda 3, 4dr Sedan 10-+ (US)	-290mm	360mm	-	873mm	847mm	-
	-11 7/16ths"	14 3/16ths"	-	34 3/8"	33 3/8"	-
Mazda 3, 5dr Hatch 09-+ (AU)	-290mm	360mm	-	873mm	838mm	-
	-11 7/16ths"	14 3/16ths"	-	34 3/8"	33 "	-
Mazda 3, 5dr Hatch 09-+ (EU)	-290mm	360mm	-	873mm	838mm	-
	-11 7/16ths"	14 3/16ths"	-	34 3/8"	33 "	-
Mazda 3, 5dr Hatch 09-+ (NZ)	-290mm	360mm	-	873mm	838mm	-
	-11 7/16ths"	14 3/16ths"	-	34 3/8"	33 "	-
Mazda 3, 5dr Hatch May 09-+ (US)	-290mm	360mm	-	873mm	838mm	-
	-11 7/16ths"	14 3/16ths"	-	34 3/8"	33 "	_